

E-ACCESS

Bluetooth Access Control Proximity Readers



Easiprox⁺
Access Control Proximity Reader
4 1/2" x 3 1/8" x 11/16"
(114 x 80 x 18 mm)
Navy blue finish



Easiprox⁺ Slim
Access Control Proximity Reader
3 7/16" x 1 3/4" x 15/16"
(88 x 44 x 23 mm)
Black finish



DG-360⁺
Access Control Proximity Reader
3 3/8" x 3 3/8" x 13/16"
(86 x 86 x 20 mm)
Black finish
European standard size



DG-365⁺
Access Control Proximity Reader
4 3/4" x 3" x 13/16"
(120 x 76 x 21 mm)
Chrome plated front trim
Logo LED indicator

Standard Features

- Allows smartphone-operated access
- Bluetooth operating range up to 50 meters
- Adjustable Auto proximity range for convenient access
- E-Access app available for easy access control and user management
- LED and built-buzzer indicate status
- 125KHz RFID technology- using EM or EM compatible cards (except model E1196)



GIANNI INDUSTRIES, INC.

Tel: +886-2-2267-7986 Fax: +886-2-2267-9876
www.gianni.com.tw inquiry1@gianni.com.tw

Bluetooth Access Control Proximity Readers

| Model | Easiprox ⁺ Slim | Easiprox ⁺ | DG-360 ⁺ | DG-365 ⁺ |
|--|--|-----------------------|--|---------------------|
| Technical Data and Functions | | | | |
| Voltage (VDC) | 12 | | | |
| Current Draw | Easiprox Slim ⁺ Standby current : 89mA/12VDC Working current (Relay active) : 103mA/12VDC | | DG-360 ⁺ Standby current : 90mA/12VDC Working current (Relay active) : 101mA/12VDC | |
| | Easiprox ⁺ Standby current : 53mA/12VDC Working current (Relay active) : 60mA/12VDC | | DG-365 ⁺ Standby current : 65mA/12VDC Working current (Relay active) : 80mA/12VDC | |
| Bluetooth Module | BLE 4.2 | | BLE 4.2 | |
| Administrator/Users | 1/200 | | 1/200 | |
| Access Modes | Smartphone Prox card | | Smartphone Prox card | |
| RFID Prox Card Read Range | 5 cm | | 3 cm | |
| Interface | REX & Door sensor input, Alarm output | | REX & Door sensor input, Alarm output | |
| Tamper Alarm | ● | | ● | |
| Door Held Open Alarm (Built-in 85 dB buzzer) | ● | | — | |
| MOSFET Relay (Prevents electromagnetic interference) | — | | ● | |
| Anti-tailgate Function | — | | ● | |
| E-Access App Functions | | | | |
| Lock Action | Keep unlocked /locked status or set relock time | | Keep unlocked/locked status or set relock time | |
| User Management | Add/Delete/View user data, grant user access for specific dates or time periods and change user passcode | | Add/Delete/View user data, grant user access for specific dates or time periods and change user passcode | |
| Audit Trail Events | 1000 | | 1000 | |
| Backup/Restore Data | ● | | ● | |

E-ACCESS

Bluetooth Access Control Proximity Keypads

Illuminated Proximity Keypads with Integrated Bluetooth



DG-170⁺

Access Control Proximity Reader/Keypad



DG-800⁺

Access Control Proximity Reader/Keypad



DG-320BLE

Access Control Proximity Readers



DG-325BLE

Access Control Proximity Readers

Standard Features





- Allows smartphone-operated access
- Bluetooth operating range up to 50 meters
- Adjustable Auto proximity range for convenient access
- E-Access app available for easy access control and user management
- LED and built-buzzer indicate status
- 125KHz RFID technology- using EM or EM compatible cards
- Keypad backlighting
- Easy data backup and restore function
- Wrong code lockout



GIANNI INDUSTRIES, INC.

Tel: +886-2-2267-7986 Fax: +886-2-2267-9876
www.gianni.com.tw inquiry1@gianni.com.tw

Specifications

| | <div>DG-170⁺</div> <div></div> | <div>DG-800⁺</div> <div></div> | <div>DG-320BLE</div> <div></div> | <div>DG-325BLE</div> <div></div> |
|-----------------------------------|--|--|---|---|
| Voltage(VDC) | 12/24 | | | |
| Bluetooth Module | BLE 4.2 Bluetooth Low Energy | | | |
| Current Draw | Standby current:56mA@12VDC ; 28mA@24VDC Working current (Relay active) : 85mA@12VDC ; 43mA@24VDC | | Standby current:43mA@12VDC ; 23mA@24VDC Working current (Relay active) : 63mA@12VDC ; 34mA@24VDC | |
| Administrator/Users | 1/200 | | | |
| Access Modes | Smartphone, RFID prox card, PIN code (4 to 8 digits) | | | |
| Interface | REX & Door sensor input, Alarm output | | | |
| Internal Alarm (85 dB) | Tamper buzzer, Door held open alarm | | | |
| Lock Action | Keep unlocked/locked status or set relock time | | | |
| User Management | Add/Delete/View user data Grant user access for specific dates or time periods Change user passcode | | | |
| Audit Trail Events | 1000 | | | |
| Mounting Style | Mullion (DG-170+), Wall switch (DG-800+) Surface mount (DG-320BLE/DG-325BLE) | | | |
| Read Range (125 KHz proximity) | 3.5 cm for RFID cards | | | |
| Dimensions | 6" x 1 3/4" x 15/16" (152 x 45 x 23 mm) | 4 13/16" x 3 1/8" x15/16" (123 x 79 x 23mm) | 4 1/2" x 2 3/4" x 1 9/16" (114 x 70 x 41 mm) | 4 3/4" x 2 15/16" x 1 13/16" (120 x 74 x 46.2 mm) |
| Material | Chrome/Gold finish | Chrome/Gold finish IP rated weatherproof | ABS | ABS / Stainless Steel |

Warranty

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original client. The GEM policy is one of continual development and improvement; therefore GEM reserves the right to change specifications without notice