ANSI Size

PBT Push Buttons

Various Selections and Colors

Standard Features

- Momentary DPDT, SPST, or SPDT contacts (Maintained switch for PBT-060B-TG)
- Stainless steel single gang plate: 4 1/2" x 2 3/4" (114x70.5mm)
- Available in LED switches & Piezo-electric switches (PBT-110-PTE, PBT-110-E)
- Optional surface mount back box provided







PBT-020B-2

- Momentary SPST, 2A/48VDC
- Flush mounted



PBT-020B-4

- Momentary DPDT, 5A/125VAC
- Flush mounted
- · Cables included



PBT-020B-4T

- Momentary DPDT, 5A/125VAC
- Flush mounted
- · Cables included
- Terminal block



PBT-060B

- Momentary DPDT, 5A/250VAC
- Flush mounted



PBT-060B-TG

- Maintained DPDT, 5A/125VAC
- Flush mounted
- Cables included
- Toggle switch



PBT-020BJ

- Momentary SPST, 5mA/12VDC
- Flush mounted



PBT-160B

- Momentary DPDT, 5A/125VAC
- Flush mounted



PBT-180B

- Momentary DPDT, 5A/125VAC
- Flush mounted
- · Cables included



PBT-060BL

- 5A/250VAC, 6A/24VDC
- Flush mounted
- Illuminated



PBT-020B-LED

- Momentary SPDT,1 A/250VAC
- Flush mounted

· Momentary DPDT,

· Bi-color LED (Green/Blue)

Optional Back Boxes



· Stainless steel, Silver

• 4 9/16" x 2 3/4" x 1 3/4" (116 x 70 x 45mm)



SMB-101 • Plastic, Black/White

• 4 1/12" x 2 3/4" x 1 3/16" (114 x 70 x 30mm)



SMB-750

- Metal, White
- 4 1/12" x 2 3/4" x 1 1/4" (114 x 70 x 32mm)

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original client. The GEM policy is one of continual development and improvement; therefore GEM reserves the right to change specifications without notice.

