Push Plate Exit Buttons

Disabled Exit Buttons

Standard Features

- All active target area
- Ideal for use in nursing homes, hospitals, and disabled/handicapped facilities
- · Surface mounted
- Momentary SPDT switch
- Stainless steel faceplate
- Adaptable to wireless (For PBT-900-1)
- Aluminum surface box: 115 x115 x 69.5mm
 Plastic surface box: 130 x 130 x 72mm







PBT-900ALU-1

- Contact rating 15A/125 or 250VAC
- Aluminum back box



PBT-900ALU-2

- Contact rating 15A/125 or 250VAC
- Aluminum back box



PBT-900ALU-3

- Contact rating 15A/125 or 250VAC
- Aluminum back box



PBT-900ALU-4

- Contact rating 15A/125 or 250VAC
- Aluminum back box



PBT-900-1

- Contact rating 15A/125 or 250VAC
- Plastic back box
- Available as a wireless exit device



PBT-900-2

- Contact rating 15A/125 or 250VAC
- Plastic back box



PBT-900-3

- Contact rating 15A/125 or 250VAC
- Plastic back box



PBT-900-4

- Contact rating 15A/125 or 250VAC
- · Plastic back box

Warranty

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original client. The GEM policy is one of continual development and improvement; therefore GEM reserves the right to change specifications without notice.

